

# ULTRA Deep Clean

## Porous Surface Deep Cleaner

### Surface Preparation

Sweep or vacuum surface to remove loose debris. Properly dilute ULTRA Deep Clean following label instructions;

Mix 3 parts of water to 1 part of ULTRA Deep Clean to make the ready-to-use cleaner.

### Application

Apply product liberally with a pump up sprayer or wet mop. Coverage will be approximately 150-300 Sq. Ft. per gallon depending on porosity of surface materials. Allow product to dwell for 15-25 minutes. DO NOT allow the product to dry during this time. Agitate the surface with a deck brush or a machine with a brush attachment. Remove slurry using a wet vacuum. Rinse thoroughly with water to remove any residue. Test for neutral pH. Rinse with additional plain water as necessary. Allow surface to dry.

### Limitations

Avoid freezing or long-term high temperature storage. ULTRA Deep Clean may etch marble, limestone and other natural stone surfaces. Test prior to use. Use of this product is NOT appropriate for aluminum as prolonged contact may cause slight surface discoloration and physical deterioration.

### Customer Service

Ultra Durable Technologies provides services and consultations on material selection, specification, troubleshooting and other information on the proper restoration and protection of tile and grout and concrete surfaces.

### Warranty

Ultra Durable Technologies' products are warranted to be of uniform quality within manufacturing tolerances. Since no control is exercised over its use, no warranty expressed or implied is made to the effects of such use. Seller and Manufacturer's obligations under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective.

See ULTRA Deep Clean Safety Data Sheet (SDS) for proper safety and handling information.

Application videos available at [www.ultraDT.com](http://www.ultraDT.com).

### Properties

Color
Amber
Mixing Ratio
3 Water:1 Concentrate
pH
.7 (Typical)
pKa
0.176
Freeze Point
<-22°F, -30°C
Odor
Mild
Corrosive
NON CORROSIVE to skin
Chemical Family
Organic Acid
Non-hazardous
WHMIS/OSHA
Coverage Rates
150-300 Sq. Ft. per mixed gallon, depending on porosity of surface
Shelf Life
12 months @ 59-77°F, 15-25°C