



BETTER BY DESIGN™



Easycove® cove base moldings are pre-formed with a patented watertight design, specifically geared for the floor and wall coatings industry.

A uniquely engineered cove base, the cove is easily coated and provides numerous benefits over traditional hand troweled and existing cove moldings currently available.

● MOISTURE LOCK-OUT

A patented design with interlocking technology, protects against moisture intrusion to dry wall, CMU, and other porous surfaces where associated hazards such as mold and mildew can occur.

● NO SEPARATION ANXIETY

Easycove® coving is manufactured to have an expansion coefficient, similar to epoxy. This feature helps to eliminate cracking and separation between dissimilar materials under thermal cycling conditions.

● TURNING A CORNER

Easycove® coving allows for greater installation convenience, as it can be mitered to accommodate inside or outside angles without the need for pre-formed corners. (Pre-formed corners available)

● MORE GREAT NEWS

Self-extinguishing - will not support combustion

3 Sizes: 1", 4" and 6" tall radius cove base

Cove radius: 1"+ Length: 48"

Cove Base wall thickness: nominal 1/4"

Total distance out from wall: 1-1/4"

Weight: approx. 0.70 lbs/ft and 0.95 lbs/ft

Cove base: 60 LF 4' pieces/box, totaling 60' / box;

One 4" box = 43 lbs and one 6" box = 65 lbs



Ensure a superior bond using our adhesive

ANTI-CAULK BEVEL

No finish caulk needed

DOVE LOCK™ BOND CHANNELS

For superior adhesion

CSP3 PROFILE

Built-in anchor profile

COVE ANCHOR

Patented Wet-Block