

SAFETY DATA SHEET

Revision Date 20-Mar-2024

1. IDENTIFICATION

Product identifier

Product Name UltraSpartic 100 Part B

Other means of identification

Part Number(s) 231105, 231109

Recommended use of the chemical and restrictions on use

Recommended use No information available.
Uses advised against No information available.

Details of the supplier of the safety data sheet

Manufacturer Address

ULTRA DURABLE TECHNOLOGIES

355 6th Ave. North Waite Park, MN 56387 320-258-2266

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

Chemical Name or Synonym:

HDI HOMOPOLYMER; HDI OLIGOMER; ALIPHATIC ISOCYANATE

2. HAZARDS IDENTIFICATION

Classification

Acute Toxicity	Category 4
Skin Sensitization	Category 1
STOT SE	Category 3

Warning



Hazard-determining components of labeling

Hexamethylene diisocyanate oligomers, Isocyanurate hexamethylene-di-isocyanate

Hazard statements

Harmful if inhaled.

May cause an allergic skin reaction.

May cause respiratory irritation.

Precautionary Statements

Prevention

Do not breathe dust/fume/gas/mist/vapors/spray.

In case of inadequate ventilation wear respiratory protection.

Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Disposa

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard description

CAUTION! HARMFUL IF INHALED. MAY CAUSE SKIN, EYE AND RESPIRATORY TRACT IRRITATION. POSSIBLE SENSITIZER. REACTS WITH COMMON MATERIALS INCLUDING WATER, ALCOHOLS, BASES AND AMINES RELEASING LARGE AMOUNTS OF CARBON DIOXIDE.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 2 Fire = 1 Reactivity = 1

HMIS-ratings (scale 0 - 4)

HEALTH	2
FIRE	1
REACTIVITY	1

Health = 2 Fire = 1 Reactivity = 1

Other hazards

Combustible liquid.

On contact with water carbon dioxide is released.

This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected human carcinogens. Asthmatic sensitization can occur from a single large inhalation exposure or from repeated lower inhalation exposures. Strict observation of exposure

limits is essential (see Section 8).

Results of PBT and vPvB assessment

PBT No. **vPvB** No.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization: Substances

CAS No. Description

28182-81-2 Hexamethylene diisocyanate oligomers, Isocyanurate

Identification number(s) EC number: 931-274-8

Chemical components		
CAS: 28182-81-2 EC number: 931-274-8	Hexamethylene diisocyanate oligomers, Isocyanurate	100%
CAS: 822-06-0 EINECS: 212-485-8	hexamethylene-di-isocyanate	< 0.2%

Additional information

Hazardous impurities: Hexamethylene diisocyanate (CAS: 822-06-0): < 0.2 %

For the wording of the listed hazard phrases refer to section 16.

4. FIRST AID MEASURES

Description of first aid measures

General information Immediately remove any clothing soiled by the product. Use appropriate

protective equipment when treating a contaminated person. Place contaminated clothing in a sealed bag for disposal. In case of irregular breathing or respiratory

arrest provide artificial respiration.

After inhalation Move the person away from the contaminated area. Fresh air and rest. Seek

immediate medical advice. Bring SDS with to show to doctor.

After skin contact Wash with soap and water. Wash immediately and thoroughly for a prolonged

period (at least 15 minutes). In case of inflammation (redness, irritation, ...) obtain

medical attention.

After eye contact Immediately rinse with plenty of running water for a prolonged period, (at least 15

minutes) while keeping the eyes wide open. If irritation persists, consult a doctor

Bring SDS with to show to doctor.

After swallowing NEVER attempt to induce vomiting. Rinse mouth out with water. Do not give

anything to drink. If necessary seek medical advice. Bring SDS with to show to

doctor.

Most important symptoms and effects, both acute and delayed:

Symptoms No further relevant information available.

Danger Skin contact may aggravate existing skin disease. Inhalation of product may

aggravate existing chronic respiratory problems such as asthma, emphysema, or

bronchitis.

Indication of any immediate medical attention and special treatment needed:

All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Treat symptomatically. No specific antidote available.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing agents Foam

Powders
Carbon dioxide
Dry chemical

For safety reasons unsuitable

extinguishing agents Water

Special hazards arising from the

substance or mixtureCombustible.

During combustion toxic vapors are released.

Duffing combustion toxic vapors are released.

Under fire conditions, corrosive fumes are emitted: oxides of nitrogen, oxides of carbon. Reacts with water releasing large amounts of carbon dioxide which may

cause pressure build-up in confined spaces.

ULTRASPARTIC 100 PART B

Revision Date 20-Mar-2024

Advice for firefighters

Protective equipment Firefighters should wear NIOSH/MSHA approved self-contained breathing

apparatus and full protective clothing.

Additional information Stay upwind. Evacuate the personnel away from the fumes.

In case of fire close by Cool down the containers/equipment exposed to heat with a water spray. Ensure

that there is NO direct contact between the water and the product. Do not breathe fumes. Do NOT attempt to fight the fire without suitable protective equipment. If there is a fire close by and if packaging has not been damaged:

Use suitable extinguishers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Personal precautionsDo not breathe gas.

Avoid any direct contact with the product. Do NOT approach from DOWNWIND.

Do NOT attempt to take action WITHOUT suitable protective equipment.

Self-contained breathing apparatus.

Wear fully protective suit.

Keep people at a distance and stay upwind.

Mark out the contaminated area with signs and prevent access to unauthorized

personnel.

Environmental precautions

Environmental precautions Contain the spilled material by binding. Do not allow to enter sewers/ surface or

ground water.

Methods and material for containment and cleaning up:

Methods for cleaning up Pump up the product into a spare container suitably labelled.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders).

Wash contaminated area with large amounts of water. Recover the cleaning water for subsequent disposal.

Dispose contaminated material as waste according to item 13.

Do not flush to drain. Spills may be reportable to the National Response Center

(800-424-8802) and to state and/or local agencies.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure good ventilation/aspiration at the workplace.

Avoid contact with water or humidity.

Avoid any direct contact with the product.

Any measure to eliminate exposure should be considered.

Very high level of containment required, except for short term exposures e.g.

taking samples (industrial use condition).

Comply with instructions for use (refer to technical sheet).

Conditions for safe storage, including any incompatibilities:

Storage The floor of the depot should be impermeable and designed to form a water-tight

basin.

Store in cool, dry conditions in well-sealed receptacles.

Store receptacle in a well-ventilated area. Store away from incompatible materials.

Requirements to be met by storerooms and receptacles

Suitable material for receptacle and pipe Epoxy-coated steel.
Unsuitable material for receptacle Polystyrene.
Store only in unopened original receptacles. Metallic drums.

Storage tank with a dry nitrogen blanket.

Packaging materials recommended

Suitable material for receptacle Aluminum.
Suitable material for receptacle Steel.
Unsuitable material for receptacle Copper.
Unsuitable material for receptacle Tin.

Specific end use(s) No further relevant information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters:

Components with limit values that require monitoring at the workplace:

The recommended limits SHOULD NOT be exceeded. Exposure limits represent regulated or recommended worker breathing zone concentrations measured by validated sampling and analytical methods, meeting the regulatory requirements. The following limits apply to this material, where, if indicated, S=skin and C=ceiling limit:

822-06-0 hexamethylene-di-isocyanate	
REL	Short-term value: C 0.14* mg/m³, C 0.02* ppm
	Long-term value: 0.035 mg/m³, 0.005 ppm
TLV	*10-min
	0.034 mg/m³, 0.005 ppm
28182-81-2 Hexamethylene diisocyanate oligomers, Isocyanurate	

TLV (Threshold Limit Value established I	oy ACGIH)	
822-06-0	hexamethylene-di-isocyanate	0.005 ppm

NIOSH-Ca (National Institute for Occupational Safety and Health)	
822-06-0	hexamethylene-di-isocyanate

Exposure controls

Personal protective equipment

General protective and hygienic measures Ensure good ventilation of the workstation.

Safety shower. Eye wash.

Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

Store protective clothing separately. Shower or take a bath at the end of work.

Breathing equipment When using a spray-gun, wear: Self-contained breathing apparatus.

In the event of insufficient ventilation: Self-contained breathing apparatus. When respirators are required, select NIOSH/MSHA approved equipment based on actual or petential sirborne concentrations and in accordance with the

on actual or potential airborne concentrations and in accordance with the appropriate regulatory standards and/or industrial recommendations.

Protection of hands Protective gloves.

The glove material must be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of

the penetration times, rates of diffusion and the degradation.

Material of gloves Suitable materials also with prolonged, direct contact (protective index 6,

> corresponding > 480 minutes of permeation time): Nitrile rubber, NBR Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior

to the application.

Eye protection Eye and face protection requirements will vary dependent upon work

environment conditions and material handling practices. Appropriate ANSI Z87 approved equipment should be selected for the particular use intended for this material. Eye contact should be prevented through use of chemical safety glasses with side shields or splash proof goggles. An emergency eye wash station must be readily accessible to the work area. Safety glasses.

Body protection Protective work clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

General Information

Appearance Clear and colorless liquid.

Form Liquid. Color Colorless.

Odor Odorless to mild odor.

pH-value Not applicable (reacts with water).

Change in condition

Melting point/Melting range < - 20 °C

Boiling point/Boiling range >220 °C (>428 °F) (at 1.33hPa) > 203 C (397 F) at 1 mmHg

Flash point 228 °C (442 °F) (EN 22719)

Flammability Class **WILL BURN**

Ignition temperature 460 °C (860 °F) (Spontaneous ignition temp)

Danger of explosion Not explosive.

Explosion limits

Oxidizing properties Not oxidizing.

Density at 25 °C (77 °F) 1.16 g/cm3 (9.68 lbs/gal)

Solubility in / Miscibility with

Water Reacts. **Ketones** Soluble. **Aromatic hydrocarbons** Soluble. Soluble.

Segregation coefficient (n-octanol/water)

Viscosity

Not applicable (reacts with water and/or octanol).

Dynamic at 25 °C (77 °F) 1200 mPas

Other information No further relevant information available.

10. STABILITY AND REACTIVITY

Reactivity

No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: Stable at ambient temperature.

Possibility of hazardous reactions

Reacts with Alcohols.

Amines. Bases.

Protic solvents.

Water and aqueous solutions. with a great release of CO2, and hence a risk of a pressure build-up in confined areas and forms an insoluble solid precipitate.

Strong acids

Strong oxidizing agents

<u>Conditions to avoid</u> Extreme heat.

Open flame. Moisture. Ignition sources.

Incompatible materialsNo further relevant information available.

Hazardous decomposition products

On thermal decomposition (pyrolysis) releases Toxic gases.

Carbon Dioxide. Nitrogen Oxides.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity LD/LC50 values

Harmful by inhalation.

To comply with regulatory guidelines, the substance was tested in a form (i.e., specific particle size distribution) that is different from the form in which the substance is placed on the market and in which it can reasonably be expected to be used. The acute inhalation toxicity of the substance is due to its local action on the distal part of the respiratory tract. As, in the conditions in which the product can reasonably be expected to be used, only a small fraction of the aerosols formed may reach this part of the respiratory tract, a correction has been made to take this difference into consideration. Based on our Expert judgment, the classification Acute inhalation toxicity category 4 is justified.

Not harmful by skin contact.

Not harmful if swallowed.

28182-81-2 Hexamethylene diisocyanate oligomers, Isocyanurate		
Oral	LD0	> 2500 mg/kg (rat) (OECD 423 (female))
Dermal	LD0	> 2000 mg/kg (rabbit) (OECD 402) > 2000 mg/kg (rat) (OECD 402)
Inhalative	LC50/4h	0.390 mg/l (rat) (OECD 403 (female))

Primary irritant effect

On the skin Not classified as irritating to skin.

(OECD 404) (rabbit)

On the eye Not classified as irritating to eyes.

(OECD 405) (rabbit)

Inhalation May cause respiratory irritation.

28182-81-2 Hexamethylene diisocyanate oligomers, Isocyanurate		
Inhalative	NOAEC/6h	3 mg/m³ (rat) ((OECD TG 403) (TRGS))

Carcinogenic categories

OSHA-Ca (Occupational Safety & Health Administration)	
Not listed.	

Sensitization

No pulmonary sensitization was observed in guinea pigs after either intradermal

injection or inhalation induction with HDI polyisocyanates.

There is no indication from reports in exposed workers that the substance can cause respiratory sensitization, if the risk management measures are respected.

May cause sensitization by skin contact.

Carcinogenicity

Not considered to be carcinogenic.

822-06-0 hexamethylene-di-isocyanate		
Inhalative	NOAEC Carc	0.164 ppm (rat) (OECD 453)

Mutagenicity

Is not considered genotoxic.

Reproductive toxicity

Is not considered hazardous to the reproduction.

822-06-0 hexamethylene-di-isocyanate		
	NOAEC Dvlp/Tera Tox	0.3 ppm (rat) (OECD 414)
Inhalative	NOAEC Maternal Tox	0.005 ppm (rat) (OECD 414)
	NOEC Fert	0.3 ppm (rat) (OECD 422)

12. ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity

The product does not have any known adverse effects on the aquatic organisms tested.

28182-81-2 Hexamethylene diisocyanate oligomers, Isocyanurate		
EC10/72h (static) 370 mg/l (Desmodesmus subspicatus) (EU C.3)		
EL50/48h (static)	127 mg/l (Daphnia magna) (EU C.2)	
ErC50(0-72h) (static)	> 1000 mg/l (Desmodesmus subspicatus) (EU C.3)	
LL0/96h	≥ 82.8 mg/l (Brachydanio rerio) (EU C.1)	

822-06-0 hexamethylene-di-isocyanate	
EC0/48h (static)	≥ 89.1 mg/l (Daphnia magna) (EU C.2)
ErC50(0-72h) (static)	> 77.4 mg/l (Desmodesmus subspicatus) (EU C.3)
LC0/96h (static)	≥ 82.8 mg/l (Brachydanio rerio) (EU C.1)
NOEC/72h (static)	11.7 mg/l (Desmodesmus subspicatus) (EU C.3)

Persistence and degradability

The product is not readily biodegradable.

28182-81-2 Hexamethylene diisocyanate oligomers, Isocyanurate	
BOD28	1 % (bacteria) ((EU C.4-E) (Unpublished report))
DT50	3 h (Photolysis) ((25 °C) (AOPWIN v1.92) (Internal evaluation)) 7.7 h (Hydrolysis) ((23 °C) (ASTM D4666) (Internal evaluation))

822-06-0 hexamethylene-di-isocyanate	
BOD28	42 % (bacteria) (EU C.4-D)
DT50	25 °C, 48.44 h (Photolysis) (AOPWIN v1.92)
	23 °C, 0.23 h (Hydrolysis) (ASTM D4666)

Behavior in environmental systems

Components

No information available.

Bioaccumulative potentialNot potentially bioaccumulable.
Log Pow, see section 9.

28182-81-2 Hexamethylene diisocyanate oligomers, Isocyanurate

BCF 3.2 (fish) (BCFWIN v. 2.17)

822-06-0 hexamethylene-di-isocyanate

BCF 58 (fish) (BCFWIN v.2.17)

Mobility in soil

28182-81-2 Hexamethylene diisocyanate oligomers, Isocyanurate

Log Koc 7.8 (.) (PCKOC v1.66)

822-06-0 hexamethylene-di-isocyanate

Log Koc 5861 (.) (PCKOC v1.66)

Other information: Formation of insoluble polyurea and/or amine derivative.

Ecotoxical effects

Behavior in sewage processing plants

28182-81-2 Hexamethylene diisocyanate oligomers, Isocyanurate

EC50/3h (static) 3828 mg/l (activated sludge) (OECD 209)

822-06-0 hexamethylene-di-isocyanate

EC50/3h (static) 842 mg/l (bacteria) (OECD 209)

Results of PBT and vPvB assessment

PBT No. **vPvB** No.

Other adverse effects No further relevant information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods:

Recommendation Discharging waste into rivers and drains is forbidden.

Incinerate at a licensed installation.

Disposal must be made according to federal, state, and local regulations.

Waste disposal key EPA Hazardous Waste - NO

Uncleaned packagingContaminated packaging materials must be disposed of in the same manner as

the product.

Recommendation Allow it to drain thoroughly.

Thoroughly emptied and clean packaging may be recycled. Disposal must be made according to official regulations.

14. TRANSPORT INFORMATION

UN Number NOT regulated.

DOT, ADR, ADN, IMDG, IATA

NOT regulated.

Proper shipping name (Technical Name)
DOT, ADR, ADN, IMDG, IATA

101109

Transport hazard class(es)

DOT, AND Class

ADR, IMDG, IATA Class NOT regulated.

Packing group

DOT, ADR, IMDG, IATA -

ULTRASPARTIC 100 PART B

Revision Date 20-Mar-2024

Environmental hazards Not applicable.

Special precautions for user Not applicable.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional informationThe above regulatory prescriptions are those valid on the date of publication of

this sheet. However, given the possible evolution of transport regulations for hazardous materials and in the event of the SDS in your possession dating back more than 12 months, it is advisable to check their validity with your sales office.

15. REGULATORY INFORMATION

National legislation

Safety, health, and environmental regulations/legislation specific for the substance or mixture

Sara Section 312

Fire Hazard NO
Reactive Hazard YES
Release of Pressure NO
Acute Health Hazard YES
Chronic Health Hazard YES

Section 355 (extremely hazardous substances)None of the ingredients are listed.

Section 313 (Specific toxic chemical listings) CERCLA RQ 100 lbs. for 822-06-0

822-06-0 hexamethylene-di-isocyanate

Carcinogenic categories

EPANot listed.IARCNot listed.NTPNot listed.

Inventory status

AICS

All ingredients are listed.

All ingredients are listed.

All ingredients are listed.

NDSL Not listed.

CIECS All ingredients are listed.
EINECS All ingredients are listed.
ELINCS All ingredients are listed.
ENCS All ingredients are listed.
KECI All ingredients are listed.
PICCS All ingredients are listed.
TSCA All ingredients are listed.

Legend

EPA - Environmental Protection Agency

IARC - International Agency for Research on Cancer

NTP - National Toxicology Program

AICS - Australian Inventory of Chemical Substances

DSL - Canadian Domestic Substance List

NDSL - Canadian Non-Domestic Substance List

CIECS - Chinese Chemical Inventory of Existing Chemical Substances

EINECS/ELINCS - European EINECS/ELINCS Listing

ENCS - Japan Existing and New chemical Substance List

KECI - Korea Existing Chemical Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

TSCA - Toxic Substances Control Act

Other regulations, limitations and prohibitive regulations

State of California, Proposition 65

Chemicals known to cause cancer Not listed.

Chemicals known to cause Not listed. reproductive toxicity for females

Chemicals known to cause reproductive toxicity for males

Not listed.

Not listed.

Chemicals known to cause Not listed.

developmental toxicity

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

Preparation Date 24-Jan-2023 Revision Date 20-Mar-2024

Revision Note General formatting updates. Updated physical and chemical properties.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet