

ULTRASPARTIC 85-EXT LO, 85-FAST LO, & 100

UltraSpartic[®] Coatings That Fit All Your Needs



ULTRA DURABLE
TECHNOLOGIES
Manufacturing Innovative Coatings

- **Extremely Durable & Chemical Resistant**
- **Resists Hot Tire Damage/ Staining**
- **Non-yellowing/UV-stable**
- **Tintable with UltraColor Pigments**



ULTRASPARTIC SOLUTIONS FOR:

- Primer Coats
- Body Coats
- Broadcast Coats
- Top Coats

ULTRASPARTIC IS OFTEN USED WITH:

- Full Broadcast Chip Flakes
- Sparse Broadcast Chip Flakes
- Quartz Granules
- UltraColor Pigments



ULTRASPARTIC: POLYASPARTIC FLOOR COATING

WITH ITS LONG WORKING TIME, **ULTRASPARTIC 85-EXT LO (US85-EXT LO)** IS IDEAL FOR LARGE JOBS AND WARM AND/OR HUMID ENVIRONMENTS.



- SOLIDS LEVEL: 85%
- DRY TIME: 12 HOURS
- WORKING TIME: 25 MINUTES
- VISCOSITY: LOW (225 CPS)
- PACKAGING: 2-GALLON AND 10-GALLON KITS
- MIXING RATIO: 1:1

ULTRASPARTIC 85-FAST LO (US85-FAST LO) DRIES QUICKLY, MAKING IT PERFECT FOR FAST RECOATING AND/OR RETURN-TO-SERVICE TIMES, COLD TEMPERATURES, AND DRY CLIMATES.

- SOLIDS LEVEL: 85%
- DRY TIME: 2 HOURS
- WORKING TIME: 12 MINUTES
- VISCOSITY: LOW (150 CPS)
- PACKAGING: 2-GALLON AND 10-GALLON KITS
- MIXING RATIO: 1:1



ITS EXTREMELY LOW ODOR AND VOCs MAKE **ULTRASPARTIC 100 (US100)** UNIQUE AND VERSATILE FOR A VARIETY OF APPLICATIONS.



- SOLIDS LEVEL: 99%
- DRY TIME: 5 HOURS
- WORKING TIME: 15 MINUTES
- VISCOSITY: MEDIUM (850 CPS)
- PACKAGING: 15-GALLON KITS
- MIXING RATIO: 2:1

ULTRACOLOR OFFERS A VARIETY OF COLOR OPTIONS!



UltraSpartics may be pigmented with UltraColor Pigment Packs to achieve a solid-colored primer, body coat, or topcoat.

Visit www.ultradt.com for more information or to find a distributor near you!

ULTRADT.COM

info@ultradt.com | 320.258.2266