

ULTRASCRAPE POLYUREA



**ULTRA DURABLE
TECHNOLOGIES**
Manufacturing Innovative Coatings

Speedy Polyurea Solutions for Concrete Floors

- Low Odor & Low Viscosity
- Rapid Dry Times
- Excellent Pigment Stability & Opacity (Hide)
- Flexible
- Non-Hazardous DOT & IATA



SOLUTIONS FOR:

- Chip Flakes
- Quartz Broadcasts
- Primer Coats



ULTRASCAPE POLYUREA IS IDEAL FOR APPLICATIONS IN WARM AND/OR HUMID ENVIRONMENTS.

- **WORKING TIME: 23 MINUTES (80°F / 55% RH)**
- **CHIP SCRAPE TIME: 1.5 HOURS (80°F / 55% RH)**
- **MIXED VISCOSITY: 750 CPS**
- **PACKAGING: 3-GALLON AND 15-GALLON KITS**
- **MIXING RATIO: 2:1**
- **SOLIDS LEVEL: 100%**
- **AVAILABLE IN MINERAL GRAY AND MEDIUM TAN**
- **COLOR CAN BE ADJUSTED WITH ULTRACOLOR UNIVERSAL PIGMENT PACKS**



DRY TIMES

Times are approximate and will vary depending on air temperature, floor temperature, and humidity.

Temperature	Relative Humidity	Working Time	Scrape Time
70°F	42%	28 min	2hr
75°F	55%	25 min	1 hr 45m
80°F	55%	23 min	1hr 30m
85°F	55%	20 min	1hr 15m
90°F	70%	16 min	1 hr

Visit www.ultradt.com for more information or to find a distributor near you!

ULTRADT.COM

info@ultradt.com | 800-722-2998