

1. IDENTIFICATION

Product identifier

Product Name

UltraScape Polyurea Part B | UDT Polyurea Part B

Other means of identification

Part Number(s)

235050, 235550, 235650, 234050, 234550, 234650

Recommended use of the chemical and restrictions on use

Recommended use

Crosslinker for polyurea floor coatings; for industrial use only

Uses advised against

Not intended for consumer use

Details of the supplier of the safety data sheet

Manufacturer Address

Ultra Durable Technologies
355 6th Ave. North
Waite Park, MN 56387
320-258-2266

Emergency telephone number

Emergency Telephone

Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

Acute Inhalation Toxicity	Category 3
Eye Irritation	Category 2
Respiratory Sensitizer	Category 1
Skin Sensitizer	Category 1A
Specific Target Organ Toxicity – Repeated Exposure	Category 2



Signal Word **Danger**

Hazard Statements

Toxic if inhaled.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause damage to olfactory and respiratory organs through prolonged or repeated exposure.

Precautionary Statements - Prevention

Avoid breathing fumes, vapor, or spray.

Use only outdoors or in a well-ventilated area. In case of inadequate ventilation, wear respiratory protection.

Wear protective gloves and clothing, eye protection, face protection.

Contaminated work clothing should not be allowed out of the workplace.

Wash hands and exposed skin thoroughly after handling.

Precautionary Statements - Response

IF INHALED: Remove victim to fresh air and keep comfortable for breathing. Seek immediate medical attention.

IF IN EYES: Rinse cautiously with running water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists, seek medical attention.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs, seek medical attention. Take off contaminated work clothing and wash before reuse.

Seek medical attention if you feel unwell.

Precautionary Statements – Storage

Store locked up in a well-ventilated place.

Keep tightly closed.

Precautionary Statements – Disposal

Dispose of contents and container to an approved waste disposal facility.

Hazards Not Otherwise Classified (HNOC) Statement

Isocyanate mists or vapors may cause reduced pulmonary function.

Overexposure (well over the PEL) may result in bronchitis, bronchial spasms, pulmonary edema, and suppression of the Central Nervous System (CNS).

Chronic overexposure to isocyanates may cause sensitization in some individuals which can result in allergic respiratory reactions (wheezing, shortness of breath, difficulty breathing), dizziness not associated to breathing difficulty, and/or feelings of body fatigue.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	Weight %
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	30 - 80
Polymeric Diisocyanatodiphenylmethane	9016-87-9	30 - 60

Trade Secret Statement (OSHA 1910.1200(i)) Specific chemical identities and concentrations for one or more listed chemicals are being withheld as trade secrets under the US regulation 29 CFR 1910.1200(i).

4. FIRST AID MEASURES**Description of First Aid Measures****Eye Contact**

Rinse thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention if irritation persists.

Skin Contact

Remove contaminated clothing. Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

Inhalation

Remove the affected individual to fresh air and keep the person calm. Assist in breathing if necessary. Seek immediate medical attention.

Ingestion

Rinse mouth and then drink 200-300 mL of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Seek immediate medical attention.

Most important symptoms and effects, both acute and delayed**Immediate First Aid Instructions**

If respiratory symptoms observed (breathing difficulty, breathlessness, asthma, chest discomfort, reduced pulmonary function, etc) treat immediately. Artificial respiration (CPR) may be necessary; only administer CPR if there is no risk of chemical transfer.

May cause irritation of the digestive tract with symptoms that include abdominal pain, nausea, vomiting, and diarrhea.

Special Instructions for Physicians

Treat symptomatically. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

Symptoms can appear later.

5. FIRE-FIGHTING MEASURES

Suitable Fire Extinguishing Media

Dry powder. Carbon Dioxide. Foam.

Unsuitable Extinguishing Media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Hazardous byproducts of fire include nitrous gases, fumes/smoke, isocyanate, vapor. Use of water during firefighting may cause rapid foaming and hardening of material and spread fire.

Protective equipment and precautions for fire-fighters

Evacuate area. Eliminate all ignition sources if safe to do so. Exercise caution when fighting any chemical fire. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Keep containers cool by spraying with water if exposed to fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation, especially in confined areas.

No open flames, no sparks, and no smoking. Evacuate area. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing fumes, gas, mist, vapor, or spray.

Environmental Precautions

Avoid release to the environment. Do not allow product to enter drains, sewers, public water, surface water, or groundwater. If contact is made, notify authorities.

Methods and material for containment and cleaning up

Use personal protective equipment as required.

Small spills must be absorbed with suitable absorbent and taken up mechanically into open containers. Open containers should be moved to a well-ventilated area; outside is recommended. Allow to stand open for 48 hours before closing. Do not make containers pressure tight. Clean affected area with an appropriate detergent mixture (90% water, 8% concentrated ammonia, and 2% detergent.) Dike large spills to contain liquid. Pump into an open container for disposal. If control of isocyanate vapor is required, blanket with protein foam or other suitable foam. Allow to stand open for 48 hours before closing. Do not make containers pressure tight. Residues may be scrubbed up with detergent mixture. Let stand 10 minutes and remove.

7. HANDLING AND STORAGE

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practices. Ensure good ventilation. Avoid formation of aerosols. When handling heated product, vapor should be ventilated and appropriate respirator should be used. Wear respirator when spraying.

Container is in danger of bursting when sealed gastight.

Protect against moisture. If bulging of drum occurs, transfer to well-ventilated area, puncture to relieve pressure. Open vent and let stand for 48 hours before resealing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Store away from water, acids and bases. Store blanketed under dry inert gas at atmospheric pressure to avoid reaction with moisture. Store in a well-ventilated place. Keep cool, 60-80F. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources.

Incompatible materials

Water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

The use of local exhaust ventilation is recommended. Eyewash stations, chemical showers recommended.

Exposure Guidelines

Chemical Name	STEL	TWA	PEL
P-MDI	Not established	0.005 ppm	CLV 0.02 ppm/0.2 mg/m ³
Diphenylmethane-4,4'-diisocyanate (MDI)	Not established	0.005 ppm	CLV 0.02 ppm/0.2 mg/m ³

Individual protection measures, such as personal protective equipment

Eye/Face Protection Protective Eyewear (chemical goggles). Face shield if splash hazard exists.

Skin and Body Protection Gloves (neoprene, nitrile rubber, pylox). Protective clothing.

Respiratory Protection If adequate ventilation is not available, or concentration is above occupational exposure limits, wear NIOSH-certified air-purifying respirator equipped with organic vapor sorbent and particulate filter. Keep in mind specific circumstances and exposure guidelines and determine and adhere to appropriate change-out schedules.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Color	Light Brown
Odor	Faint, Aromatic
Melting Point	5°C (41°F)
Boiling Point	200°C (392°F)
Flammability	Not flammable
Upper flammability limit	No information available
Lower flammability limit	No information available
Flash Point	Approximately 200°C (392°F)
Autoignition Temperature	> 250°C
Decomposition Temperature	No information available
pH	> 7
Dynamic viscosity	200 cPs
Kinematic Viscosity	No information available
Solubility	Reacts with water
Partition coefficient n-octanol/water (Log Pow)	No information available
Vapor Pressure	0.00001 mmHg
Density	1.23 g/cm ³ / 10.17 lb/gal
Relative Density	1.22

10. STABILITY AND REACTIVITY

Reactivity

Reacts with hydroxyl groups (water, acids, bases) to produce carbon dioxide and reacts amine groups. May foam rapidly. Product is otherwise unreactive under normal conditions of use, storage, and transport.

Chemical Stability

Product is stable under normal conditions of use, storage, and transport.

Hazardous reactions

Reacts with water, forming carbon dioxide and risk of bursting. Reacts with alcohols, acids, amines, and alkaline materials. Exothermic reaction risk. Polymerization risk.

Conditions to Avoid

Moisture.

Incompatible materials

Acids. Amines. Alcohols. Water. Alkaline materials. Strong bases.

Hazardous decomposition products

Carbon monoxide, carbon dioxide, nitrogen oxide, hydrogen cyanide, nitrogen oxides, aromatic isocyanates, gases, vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Inhalation of liquid material or gas, vapor, or mist
Eye Contact	Liquid material splash or gas, vapor, or mist
Skin Contact	Liquid material splash or liquefied gas
Ingestion	Liquid material

Numerical values of toxicity – Component information

Chemical Name	Oral LD ₅₀	Dermal LD ₅₀	Inhalation LC ₅₀
P-MDI	31,600 mg/kg (Rat)	--	>50 mg/L (Rat, vapor)
Diphenylmethane-4,4'-diisocyanate (MDI)	4,130 mg/kg (Rat)	>9,400 mg/kg (Rabbit)	1.96 mg/L (Rat, vapor, 4h)

Skin Corrosion/Irritation	Not Classified
Serious Eye Damage/Irritation	May cause serious eye irritation
Respiratory or Skin Sensitization	May cause an allergic skin reaction or asthmatic symptoms; May cause an allergic skin reaction.
Germ Cell Mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive Toxicity	Not classified
STOT – Single Exposure	Not classified
STOT – Repeated Exposure	May cause respiratory sensitization and asthmatic symptoms
Aspiration Hazard	Not classified

Numerical measures of toxicity – Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Chemical Name	Oral LD ₅₀	Dermal LD ₅₀	Inhalation LC ₅₀
UltraScape Polyurea Part B UDT Polyurea Part B	4,701.6 mg/kg	>9,400 mg/kg	2.38 mg/L

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Toxic if inhaled

12. ECOLOGICAL INFORMATION

Ecotoxicity

It is unlikely that this product is harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Chemical Name	Algae/aquatic plants	Fish	Crustacea
P-MDI	--	LC ₅₀ > 1000 mg/L (96h, Brachydanio rerio)	EC ₅₀ > 1000 mg/L (24h, Daphnia)
Diphenylmethane-4,4'-diisocyanate (MDI)	--	--	--

Chemical Name	Algae/aquatic plants	Fish	Crustacea
UltraScape Polyurea Part B UDT Polyurea Part B	--	LC ₅₀ > 1,000 mg/L (96h, Brachydanio rerio) OECD Guideline 203, static	EC ₅₀ > 1,000 mg/L (24h, Daphnia magna) OECD Guideline 202, static

Persistence and Degradability

Poorly biodegradable. Unstable in water. Elimination data also refer to products of hydrolysis.

Bioaccumulation Potential

Chemical Name	Partition Coefficient n-octanol/water (Log P _{ow})
P-MDI	4.5 (at 25°C)
Diphenylmethane-4,4'-diisocyanate (MDI)	Not established

Assessment

Not readily biodegradable. Product is unstable in water.

Mobility in Soil

The substance will not evaporate into the atmosphere from the water surface. Adsorption to solid soil phase is not expected.

Other adverse effects**Elimination information**

0% BOD of the ThOD (28d, aerobic, activated sludge, OECD Guideline 302 C).

Water hydrolysis

In contact with water the substance will hydrolyze slowly.

$t^{1/2} = 20\text{h}$ (25°C)

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods**Disposal of Wastes**

Disposal should be in accordance with applicable regional, national, and local laws and regulation. Incinerate or dispose of in a licensed facility. Do not discharge product into sewer system.

Contaminated Packaging

Do not reuse container. Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer, or an approved landfill. Do not refill or clean containers of residue. Do not burn empty drums or cut open with gas or electric torch as toxic decomposition products may be liberated.

14. TRANSPORT INFORMATION

UN Number	Not regulated for transport
UN Proper Shipping Name	Not Applicable
Transport Hazard Class(es)	
DOT	Not applicable
IOMDG	Not applicable
IATA	Not applicable
Packing Group	
DOT	Not applicable
IMDG	Not applicable
IATA	Not applicable
Environmental Hazards	None

NOTE Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100-177, IMDG, IATA, EC, Canadian TDG, and United Nations TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

15. REGULATORY INFORMATION

Chemical Inventories**TSCA**

All components of this product are listed on the TSCA Inventory.

US Federal Regulations**SARA 313**

Section 313 of the Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations. Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No
Carcinogenicity	No
Respiratory or Skin Sensitization	Yes
Germ Cell Mutagenicity	No
Serious Eye Damage/Irritation	Yes

US State Regulations

California Proposition 65 – This product contains substances believed by the state of California to cause cancer, developmental, and/or reproductive harm.

State Right to Know

New Jersey	Diphenylmethane-4,4'-diisocyanate (MDI) P-MDI	CAS 101-68-8 CAS 9016-87-9
	Methylenediphenyl diisocyanate	CAS 2647-40-5
Pennsylvania	Diphenylmethane-4,4'-diisocyanate (MDI) P-MDI	CAS 101-68-8 CAS 9016-87-9

HMIS Hazard codes

Health	2
Fire	1
Reactivity	1

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

Preparation Date	20-Mar-2024
Revision Date	9-July-2026
Revision Note	General formatting updates; updated hazards information, updated chemical composition information.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet